



## AMP 200<sup>®</sup>

### GM tube-based rate meter

- designed specifically to be used in high dose rate fields
- features linear response from 5R/h to 10 000 R/h (2.5 mSv/hr to 100 Sv/hr)
- real-time monitor applications

- rugged construction, waterproof detector housing and cable
- quick-disconnect connectors allow customization of cable length and facilitate easy decontamination
- built-in communication port for use with DDC-16, WRM transmitter...
- «smoothed» digital display offers accurate, stable readings
- user-selectable internal alarm threshold

The AMP-200 provides real-time remote monitoring. Local readout of hand-held meter allows for use as a portable survey instrument. More importantly, since the probe's sensitive electronics are located far from the high field (25 to 350 feet away), they are not subject to destructive gamma exposure. The probe head may be placed directly into a filter cube or against a resin tank.

## Radiological characteristics

---

- detector: energy compensated GM-tube
- detection range ( $\pm 10\%$ ): 0.5 R/h to 10 000 R/h
- energy range: sensitivity: 11 cps per R/h
- detector life time: 20 R/h field for three years

## Electrical characteristics

---

- power supply: 9 Volts (supplied by a 9 Volt battery located in the meter case)
- optional 9 Volt AC adapter available
- battery life: approximately 50 hours of continuous use

## Mechanical characteristics

---

- meter dimensions (w x h x d): 6.85 x 11.93 x 1.25 cm (2.7 x 4.7 x 1.25 in)
- probe head length: 10,79 cm (4.25 in)
- diameter: 2.03 cm (0.8 in)
- standard cable length: 7.62 m (25 ft)
- maximum cable length: 106.68 m (350 ft)

## Environmental characteristics

---

- temperature:  $-10^{\circ}$  to  $50^{\circ}\text{C}$  (15 to  $120^{\circ}\text{F}$ )
- relative humidity: 10 to 95% RH (non-condensing)

Ⓑ Exclusively sold in North  
and South America